



**NOTES:**

1. CONTRACTOR SHALL PERFORM PRUNING DURING ONE - YEAR WARRANTY PERIOD.
2. WHERE EXISTING PARKWAY TREES HAVE BEEN ROOT PRUNED, INSTALL CONTINUOUS, LINEAL ROOT BARRIER ADJACENT TO THE CURB AND / OR SIDEWALK.
3. LENGTH AND LOCATION OF ROOT BARRIER TO BE DETERMINED BY CITY ENGINEER.
4. ROOT SEALER SHALL BE APPROVED BY THE CITY ENGINEER AT LEAST 48 HOURS IN ADVANCE OF THE PRUNING OPERATION. SHALL BE APPLIED TO ALL CUT ROOT AREAS WHICH ARE LARGER THAN 2" IN DIAMETER. THE SEALER SHALL BE APPLIED AS SOON AS PRACTICAL AFTER THE CUTS HAVE BEEN MADE.
5. ROOT BARRIERS SHALL BE FABRICATED FROM A HIGH DENSITY, HIGH IMPACT PLASTIC AND BE EXPRESSLY DESIGNED FOR THE PURPOSE OF ROOT DEFLECTION.

TITLE:

# LANDSCAPING - PRUNING

DRAWN BY: <b>LOUIE C. GUEVARA</b>	SCALE: <b>NONE</b>
REVIEWED BY: <b>DAVID RUBCIC</b>	REVISED: <b>OCTOBER, 2013</b>

APPROVED: \_\_\_\_\_

*David Rubcic* 12-20-13

CITY ENGINEER: DAVID RUBCIC LIC. NO. 57601 EXP. DATE: 12-31-2013      DATE

STANDARD PLAN

## H-3

**CITY OF HOLLISTER  
ENGINEERING DEPARTMENT**

SHEET 1 OF 1