



NOTES:

1. CONTRACTOR SHALL PERFORM PRUNING DURING ONE-YEAR WARRANTY PERIOD.
2. WHERE EXISTING PARKWAY TREES HAVE BEEN ROOT PRUNED, INSTALL CONTINUOUS, LINEAL ROOT BARRIER ADJACENT TO THE CURB AND/OR SIDEWALK.
3. LENGTH AND LOCATION OF ROOT BARRIER TO BE DETERMINED BY CITY ENGINEER.
4. ROOT SEALER SHALL BE APPROVED BY THE CITY ENGINEER AT LEAST 48 HOURS IN ADVANCE OF THE PRUNING OPERATION, AND SHALL BE APPLIED TO ALL CUT ROOT AREAS WHICH ARE LARGER THAN 2" IN DIAMETER. THE SEALER SHALL BE APPLIED AS SOON AS PRACTICAL AFTER THE CUTS HAVE BEEN MADE.
5. ROOT BARRIERS SHALL BE FABRICATED FROM A HIGH DENSITY, HIGH IMPACT PLASTIC AND BE EXPRESSLY DESIGNED FOR THE PURPOSE OF ROOT DEFLECTION.

TITLE:

LANDSCAPING-PRUNING

DRAWN BY: STAFF	SCALE: NONE
REVIEWED BY: DANNY HILLSTOCK	REVISED: OCTOBER, 2019

APPROVED:

Danny Hillstock 11-5-19

CITY ENGINEER: DANNY HILLSTOCK LIC. NO. 70847 DATE

STANDARD PLAN

H-3

CITY OF HOLLISTER
ENGINEERING DEPARTMENT

SHEET 1 OF 1